

## 自然給排気口 1

排気方向の通気量試験です。

品名	型式					圧力損失 係数 $\xi$	風量(m <sup>3</sup> /h)					相当開口 面積cm <sup>2</sup>	a
	UK-基本型	ダクトφ	仕様型	ダンパー	防火ダンパー仕様		10Pa	20Pa	30Pa	40Pa	50Pa		
WC型フード付ガラリ	WCEN	100	S			3.13	52.8	74.7	91.5	105.6	118.1	35.93	16.7
	WCEN	150	S			2.59	129.3	182.9	224.0	258.7	289.2	88.00	40.9
	WCEN	100	S	FD	特定防火設備該当品	5.02	44.0	62.2	76.1	87.9	98.3	29.91	13.9
	WCEN	150	S	FD	特定防火設備該当品	3.90	110.4	156.1	191.2	220.7	246.8	75.09	34.9
スクエアスリムフード	SQEN	100	B			22.24	22.5	31.8	38.9	44.9	50.2	15.28	7.1
	SQEN	150	B			55.66	32.3	45.6	55.9	64.5	72.1	21.95	10.2
	SQEN	100	B	FD	特定防火設備該当品	22.10	22.5	31.8	38.9	44.9	50.2	15.28	7.1
	SQEN	150	B	FD	特定防火設備該当品	51.99	33.2	47.0	57.5	66.4	74.3	22.59	10.5
M型フード付ガラリ 防音タイプ	MBON	100	B			10.78	31.3	44.3	54.2	62.6	70.0	21.30	9.9
	MBON	150	B			39.87	38.0	53.7	65.7	75.9	84.9	25.82	12.0
	MBON	100	B	FD	特定防火設備該当品	15.22	26.9	38.0	46.6	53.8	60.1	18.29	8.5
	MBON	150	B	FD	特定防火設備該当品	38.19	38.9	55.0	67.4	77.8	87.0	26.47	12.3
M型フード付ガラリ	MZEN	100	B			2.73	55.0	77.8	95.3	110.1	123.0	37.44	17.4
	MZEN	150	B			3.03	123.3	174.4	213.6	246.7	275.8	83.92	39.0
	MZEN	100	B	FD	特定防火設備該当品	4.42	45.9	64.9	79.4	91.7	102.5	31.20	14.5
	MZEN	150	B	FD	特定防火設備該当品	4.33	107.2	151.6	185.7	214.4	239.7	72.94	33.9
W型フード付ガラリ	WEN	100	B			3.19	52.2	73.8	90.4	104.4	116.7	35.50	16.5
	WEN	150	B			3.23	119.9	169.5	207.6	239.7	268.0	81.55	37.9
	WEN	100	B	FD	特定防火設備該当品	4.59	45.2	64.0	78.3	90.4	101.1	30.77	14.3
	WEN	150	B	FD	特定防火設備該当品	4.31	107.5	152.1	186.2	215.0	240.4	73.16	34.0
フラット型スリムフード	FSN	100	B			14.69	27.2	38.5	47.1	54.4	60.8	18.51	8.6
	FSN	150	B			17.05	57.2	81.0	99.1	114.5	128.0	38.95	18.1
	FSN	100	B	FD	特定防火設備該当品	15.81	26.3	37.1	45.5	52.5	58.7	17.86	8.3
	FSN	150	B	FD	特定防火設備該当品	15.35	60.1	85.0	104.1	120.2	134.4	40.88	19.0
フラット型スリムフード水切付	FSEN	100	B			14.69	27.2	38.5	47.1	54.4	60.8	18.51	8.6
	FSEN	150	B			17.05	57.2	81.0	99.1	114.5	128.0	38.95	18.1
	FSEN	100	B	FD	特定防火設備該当品	15.81	26.3	37.1	45.5	52.5	58.7	17.86	8.3
	FSEN	150	B	FD	特定防火設備該当品	15.35	60.1	85.0	104.1	120.2	134.4	40.88	19.0
フラット型スリム風防付	FWSN	100	B			16.26	25.9	36.7	44.9	51.9	58.0	17.64	8.2
	FWSN	150	B			13.90	62.9	89.0	109.0	125.9	140.7	42.82	19.9
	FWSN	100	B	FD	特定防火設備該当品	17.96	24.7	34.9	42.7	49.3	55.2	16.79	7.8
	FWSN	150	B	FD	特定防火設備該当品	15.42	60.1	85.0	104.1	120.2	134.4	40.88	19.0
フラット型スリム風防水切付	FWSEN	100	B			16.26	25.9	36.7	44.9	51.9	58.0	17.64	8.2
	FWSEN	150	B			13.90	62.9	89.0	109.0	125.9	140.7	42.82	19.9
	FWSEN	100	B	FD	特定防火設備該当品	17.96	24.7	34.9	42.7	49.3	55.2	16.79	7.8
	FWSEN	150	B	FD	特定防火設備該当品	15.42	60.1	85.0	104.1	120.2	134.4	40.88	19.0
フラット型フード付ガラリ	FN	100	S			6.60	38.9	55.0	67.4	77.8	87.0	26.47	12.3
	FN	150	S			14.40	62.0	87.7	107.4	124.0	138.6	42.17	19.6
	FN	100	S	HD	簡易ダンパー	8.34	35.1	49.6	60.8	70.2	78.5	23.88	11.1
	FN	150	S	HD	簡易ダンパー	15.71	59.5	84.1	103.0	118.9	132.9	40.45	18.8
フラット型フード水切付ガラリ	FEN	100	S			6.60	38.9	55.0	67.4	77.8	87.0	26.47	12.3
	FEN	150	S			14.40	62.0	87.7	107.4	124.0	138.6	42.17	19.6
	FEN	100	S	HD	簡易ダンパー	8.34	35.1	49.6	60.8	70.2	78.5	23.88	11.1
	FEN	150	S	HD	簡易ダンパー	15.71	59.5	84.1	103.0	118.9	132.9	40.45	18.8
フラット型風防付ガラリ	FWN	100	S			3.36	51.2	72.5	88.7	102.5	114.6	34.86	16.2
	FWN	150	S			5.82	93.6	132.4	162.1	187.2	209.3	63.69	29.6
	FWN	100	S	HD	簡易ダンパー	5.16	43.0	60.8	74.5	86.0	96.2	29.26	13.6
	FWN	150	S	HD	簡易ダンパー	7.54	83.8	118.5	145.2	167.6	187.4	57.02	26.5
フラット型風防水切付ガラリ	FWEN	100	S			3.36	51.2	72.5	88.7	102.5	114.6	34.86	16.2
	FWEN	150	S			5.82	93.6	132.4	162.1	187.2	209.3	63.69	29.6
	FWEN	100	S	HD	簡易ダンパー	5.16	43.0	60.8	74.5	86.0	96.2	29.26	13.6
	FWEN	150	S	HD	簡易ダンパー	7.54	83.8	118.5	145.2	167.6	187.4	57.02	26.5
U型フード付ガラリ	UGEN	75	S			10.76	18.3	25.9	31.8	36.7	41.0	12.48	5.8
	UGEN	100	S			6.53	39.2	55.5	67.9	78.4	87.7	26.68	12.4

注意 上記試験成績は、製品の改良などにより予告無く数値の変更がある場合があります。予めご了承下さい。

簡易ダンパー仕様製品は、防火設備または特定防火設備が要求される場合には使用できません。